

olivetti



PR2 E

SPECIALISED PRINTER

The **PR2 E** family is a line of specialised models addressing different user needs, **designed to print on a multitude of paper formats** from single sheet documents to passbooks and multi-copy forms with consistent quality and **extreme easy of use**.

Furthermore the **PR2 E** family is able to read **MICR**, **CMC7** and **E13B** code lines as well as **magnetic strips**, either horizontal or vertical, normally found on passbooks.

The top configuration of **PR2 E** provides **duplex scanning in a single pass** for documents with widths up to 210 mm.

THE MOST-USED PRINTER IN THE BANKING ENVIRONMENT

ULTRA FAST AUTO ALIGNMENT FOR THE BEST PERFORMANCE

ONE OF THE MOST SILENT PRINTERS OF ITS CATEGORY (<52DBA)

EXTREMELY USER FRIENDLY

HIGH RELIABILITY



ADVANCED PAPER HANDLING for the automatic alignment of any type of document plus double face scanner



SLOT for optional supplementary parallel or USB plus second serial interface



DESIGN: compact and elegant. Minimum dimensions and excellent performance

TECHNICAL SPECIFICATIONS

GENERAL	Technology	- 24-pin dot matrix	Emulation	- Olivetti Standard + IBM PP & X24
	Resolution	240 x 360 dpi		- IBM 9068 + IBM PP & X24
	Font	- OCR A-B	Interfaces	- SNI 4915
		- ROMAN		- Standard: RS232 serial
	- Sans Serif	- Optional: USB place + second serial		
	- Italic	IEEE 1284 parallel		
	Printing speed at 10 cpi	- HSD: 350 cps - Draft: 260 cps - NLQ: 130 cps - LQ: 87 cps	Noise level	< 52 dBA (ISO 7779 with ECMA 132 text)
	Pitch	10 - 12 - 15 - 16,6 - 17,1 cpi	Voltage	- Built-in power supply 110/240V, 50/60Hz
	Line length	258,76 mm (94 columns at 10 cpi)		
	Line spacing	1/5", 1/6", n/216", n/240"	Power consumption	- Stand-by: 15W - Printing: 70W max
Copies	Original + 4 copies	Certifications	- IMQ, UL, CSA, FCCA, CE ISO 9001: 2000	
Ribbon cartridge	3,5 million characters			
Document Handling	- Feed width: 245 mm	Dimensions (WxDxH)	384 x 280 x 204 mm	
	- Completely flat paper feed	Weight	10.5 kg	
	- Automatic insertion with autoborder - Automatic document-thickness monitoring			
SCANNER	Contact scanner	- CIS Technology	Scanning Speed	- 8 inch/s single face
	Resolution	8 dots/mm (200 dpi)		- 5 inch/s double face
	Light Source	- Red (green or infrared optional)	Connection	- Parallel ECP or USB 2.0
	Tones B/V	- Up to 256 level grey scale	Acquisition Format	- (W) 65÷210mm, (H) 70÷297 mm

Product performances are referred to an appropriate use under optimal conditions. With the right to change technical specifications. The registered trademarks are the property of their respective owners.
PR2 E is distributed by Olivetti S.p.A.
(10/06) - Code: 5000502-02

OLIVETTI S.P.A.
VIA JERVIS 77
10015 IVREA (TO) ITALY
www.olivetti.com